

DIRTMASTER

KWIK-WAY

A HitchDoc COMPANY

Standard Features:

- **Limitless Mobility** – Tow around the field, through the woods and then to a suburban backyard with an ATV/UTV, lawn tractor, truck or car at speeds up to 45 mph.*
- **Minimal disturbance** – Leave little to no marks with this compact and light-footed backhoe. Don't be concerned about ripping up lawn or effecting landscaping.
- **Solid Stance & Base** – Two pairs of stabilizers—one larger hydraulic pair positioned near the front and another manual pair toward the back of the machine—make for a solid working platform across any surface.
- **Easy Operation** – A beginner can easily learn and smoothly operate this backhoe with minimal experience by using the direction map that's installed next to the hydraulic levers.
- **Overbuilt to Outlast** – Decades have proven an established design and then manufactured from US prime steel and shipped from central Midwest USA.

- **Best-In-Class Motor** – Honda® engines are some of the most reliable small gas engines available—and arguably one of the best.
- **Long Lasting Finish** – A baked on Fire Engine Red powder-coat finish will resist damage and maintain through the toughest elements.
- **Bucket Variations** – Comes standard with a 12" bucket but can easily switch to a ripping tooth or other bucket widths in minutes.
- **Safe Transportation** – Use the lock pins on the stabilizers, boom and swing, along with the safety chains on the 2" ball coupler for a safe and smooth towing experience.

**Conquer any terrain
with the ultimate
towable
backhoe!**



DIRTMASTER



KWIK-WAY
A HitchDoc COMPANY

I-90 & US 71 | Jackson MN

131 County Road 34 E | P.O. Box 179 | Jackson, MN 56143

800.446.8222 | 507.847.4049 | Fax 507.847.5100

sales@HitchDoc.com | ISO 9001 Certified

www.KwikWayBlades.com

MADE IN
USA

DIRTMASTER

KWIK-WAY

A HitchDoc COMPANY



Mechanical Specifications

Engine - Manual start with low oil indicator and shutdown.
Max HP - 8.4HP / 3600 rpm
Torque - 14.1 ft. lbs. / 2500 rpm
Fuel Capacity - 1.6 Gallons
Oil Capacity - 1.16 qt 10W30
Tire size - 4.80/4.00 Pneumatic
Digging Depth - 78"
Horizontal Reach - 100"
Ripping Force - 2600 lbs.
Max Digging Radius - 140°
Lubrication - 25 Grease fittings at pivot points
Bucket Rotation - 147°
Tow Ball Size - 2" Ball
Towing Speed - 45 mph max* (10 mph with ATV/UTV)
Hydraulic Stabilizer Width - Down 100", Up (transport) 45"
Dry Weight - 1,175 lbs
Operation Weight - 1,260 lbs
Collapsed /Storage Dimensions - L 120" x W 64" x H 70"

Hydraulic Specifications

Hydraulic Tank - 12.5 gallon capacity
Hydraulic System - 13.93 gallon capacity (including tank, cylinders, hoses, filter)
Hydraulic Fluid Filter - 10 micron filter
Gear Pump - Single stage
Hydraulic Fluid - Universal Hydraulic Fluid (all temps)

Options

53-0012 - 9" Bucket
53-00321 - 16" Bucket
53-01511 - 14" Ripper Tooth
53-01611 - Fenders with lights kit

DIRTMASTER



For more information, contact your local dealer

www.KwikWayBlades.com

MADE IN
USA